




Vcore

Your Phone. Your Monitor.


Lightweight yet powerful, Vcore is more than just a video transmission system – it's your creative companion, keeping you in perfect sync with your vision while streamlining and simplifying both your setup and post-production. Imagine crystal-clear 4K30 monitoring in the palm of your hand. Your mobile device instantly becomes a professional-grade portable monitor, powered by our intuitive HollyView app. This revolutionary transmission system seamlessly merges HD monitoring, image transfer and versatile recording capabilities, empowering creators to see everything and create anywhere.



4K30 / HD Monitoring



1 TX & 4 Apps



Proxy Recording



ProRes Capture



Smart Media
Management



Instant Share & Stream

SPECIFICATIONS

Interface	HDMI IN: HDMI 1.4b POWER IN: USB-C USB OUT: USB 3.0 SD Card Slot
HDMI Input Resolution	720p50/59.94/60 1080p23.98/24/25/29.97/30/50/59.94/60 3840*2160p23.98/24/25/29.97/30
USB-C Output Resolution	720p50/59.94/60 1080p23.98/24/25/29.97/30/50/59.94/60 3840*2160p23.98/24/25/29.97/30
Wireless Transmission Resolution	720p50/59.94/60 1080p23.98/24/25/29.97/30/50/59.94/60 3840*2160p23.98/24/25/29.97/30 (Supported only with Pyro series receivers)
Power Supply	USB-C Output: 5V - 13V Built-in Battery: 3.4V - 4.2V
Battery Capacity	5150 mAh
Working Time	6 hours
Power Consumption	< 4.5W
Net Weight	220g
Dimensions	110*70*27.2mm (4.33 × 2.76 × 1.07")
Frequency Band	5.15 - 5.85 GHz
Transmit Power	≤ 21.5 dBm
Receiver Sensitivity	-93 dBm
Transmission Latency	≤ 80ms
Bandwidth	20 MHz
Operating Temperature	-10 °C - 45 °C
Storage Temperature	-40 °C - 60 °C

* The data provided above is based on Hollyland laboratory testing results.