



# Cosmo C1

1000ft Wireless SDI&HDMI Transmission System, transformed by Hollyland's HEVO wireless transmission technology, offers a new standard for real-time video monitoring and a simplified solution to stream and cloud-share your video works.



1000ft



Direct UVC Livestream



HEVO Solution



Seamless Frequency Switching



40ms Latency



HDMI + SDI + SDI LOOPOUT

[www.hollyland-tech.com](http://www.hollyland-tech.com)



- Ultra-low Latency, As Low As 40ms
- 1,000ft Wireless Transmission Range (LOS)
- Embedded UVC for Direct Live Streaming (P format Only)
- Three Power Supply Options: DC Adaptor, L-series Battery, and USB C
- Auto Channel Switching
- Low-Battery Indicator
- HDMI&SDI In/Out + SDI Loopout
- Seamless Channel Switching

Item	Parameter
<b>Power Supply</b>	DC Power Input 6~16V; USB Type-C Power Supply 5V/2A; Battery Power Supply 6-16V
<b>Power Consumption</b>	<9W
<b>Dimension (mm)</b>	115L*70W*32H (The Battery Plate Exclude)
<b>Frequency</b>	5.1GHz~5.8GHz
<b>Transmission Latency</b>	≈40ms
<b>Bandwidth</b>	20MHz
<b>Weight</b>	214g (Without Exterior Antenna); 210g (Without Exterior Antenna)
<b>TX Input Video Format</b>	HDMI:480p60; 576p50; 720p50/59.94/60; 1080i50/59.94/60; 1080p23.98/24/25/29.97/30 1080p50/59.94/60 SDI:1080p60/59.94/50(Level A); 1080p60/59.94/50(Level B); 1080i60/59.94/50; 1080p30/29.97/25/24/23.98; 720p60/59.94/50; 1080psf30/29.97/25/24/23.98
<b>RX Output Video Format</b>	HDMI:480p60; 576p50; 720p50/60; 1080i60/60; 1080p24/25/30; 1080p50/60 SDI:1080p60/50(Level A); 1080i60/50; 1080p30/29/25/24; 720p60/50